

LCOS 10.94

R&S® LANCOM WLC-2000

Centralized Wi-Fi management of large wireless networks



Do you want full control with a low workload? As a central Wi-Fi controller, the WLC-2000 gives you exactly that. Networks of 25 to 2,000 access points are easily managed and controlled centrally. New access points are automatically put into operation in the network via zero-touch deployment and supplied with suitable configurations. In operation intelligent features such as roaming optimization and the selection of the best frequency band and Wi-Fi channel ensure optimum utilization even in complex wireless networks. The R&S® LANCOM WLC-2000 thus saves the administrator time and provides the user the best Wi-Fi experience.

- ▶ Centralized firmware rollout, monitoring & management of 25 up to 2,000 access points
- ▶ Zero-touch deployment of access points
- ▶ Integrated R&S® LANCOM Public Spot XL Option
- ▶ Optimized roaming behavior of Wi-Fi clients through IEEE 802.11r and OKC
- ▶ Extensive VLAN, RADIUS, and IEEE 802.1X/EAP features
- ▶ Maximum operational security without single point of failure
- ▶ High availability of the central Wi-Fi management with High Availability Clustering Option

R&S® LANCOM WLC-2000

Central firmware rollout, monitoring & management

Positioned locally, the R&S® LANCOM WLC-2000 centrally configures and controls up to 2,000 access points and WLAN routers, so relieving the workload on network administrators and bringing massive time savings. WLAN controllers ensure uniform network control, security and reliability.

Zero-touch deployment

Quick and easy network integration of new access points as well as automatic provision of the configuration—without manual intervention. Once authenticated with the network, the Wi-Fi device immediately receives the appropriate configuration from the R&S® LANCOM WLC-2000.

Integrated Public Spot XL Option

Thanks to the integrated hotspot functionality, the R&S® LANCOM WLC-2000 is ideal for providing public Internet access for visitors, customers or other short-term network users. The user benefits from a secure and convenient hotspot and the hotspot provider can be sure that his own network remains securely separated.

Optimized roaming behavior of WLAN clients

R&S® LANCOM WLAN controllers enable communications between managed access points and WLAN routers. This ensures that clients moving between two radio fields are efficiently transferred from one Wi-Fi device to the next—without disconnections.

VLAN-, RADIUS-, and IEEE 802.1X/EAP functions

A comprehensive array of virtualization and security features allows the highly efficient design of Wi-Fi networks in close accordance with the company's own security policies. The integrated VLAN feature supports multiple securely isolated Wi-Fi networks on a shared infrastructure. Professional security features give administrators precise control over who is authorized for network access.

Highest operational security

The R&S® LANCOM Smart Controller principle ensures the highest operational reliability: While the administrative data are routed through the controller, client payload data are sent directly from the access point to the router. If a controller fails, the access point switches to “stand-alone mode” and the communication between the client and access point remains intact. This avoids downtimes during everyday business due to employees losing access to the network or the failure of WLAN-controlled production facilities.

High availability

Combined with the R&S® LANCOM High Availability Clustering option, multiple WLAN controllers are grouped into one highly available device group. In this way, configuration changes, features and enhancements made on one WLC are automatically transferred between the other WLCs in the cluster: Not having to make manual changes on each individual device means massive time savings for administrators.

Maximum future viability

From the very start, R&S® LANCOM products are designed for a product life of several years. They are equipped with hardware dimensioned for the future. Even reaching back to older product generations, updates to the R&S® LANCOM Operating System—LCOS—are available several times a year, free of charge and offering major features.

R&S® LANCOM WLC-2000

WLAN profile settings*	
Radio channels 6 GHz	Up to 24 non-overlapping channels (EU; 20 MHz channel width)
Radio channels 5 GHz	Up to 26 non-overlapping channels (available channels and further obligations such as automatic DFS dynamic channel selection depending on national regulations)
Radio channels 2.4 GHz	Up to 13 channels, max. 3 non-overlapping (depending on country-specific restrictions)
Concurrent WLAN clients	Depends on the access points in operation
IEEE 802.11u	Managed R&S® LANCOM Access Points support the WLAN standard IEEE 802.11u (Hotspot 2.0) which allows mobile clients a seamless transition from the cellular network into WLAN hotspots. Authentication methods using SIM card information, certificates or username and password, enable an automatic, encrypted login to WLAN hotspots of roaming partners - without the need to manually enter login credentials
Roaming	Seamless handover between radio cells, IAPP support with optional restriction to an ARF context, IEEE 802.11d support
Opportunistic Key Caching	Opportunistic key caching allows fast roaming processes between access points. WLAN installations utilizing a WLAN controller and IEEE 802.1X authentication cache the access keys of the clients and are transmitted by the WLAN controller to all managed access points
Fast roaming	Based on IEEE 802.11r, allows fast roaming procedures between access points. This is possible by using IEEE 802.1X authentication or pre-shared keys in controller based WLAN installations, which save the access keys temporarily and distribute them to the managed access points.
Security	WPA3-Personal, IEEE 802.11i / WPA2 with passphrase (WPA2-Personal) or IEEE 802.1X (WPA3-Enterprise, WPA2-Enterprise) and hardware-accelerated AES, closed network, WEP64, WEP128, WEP152, user authentication, IEEE 802.1x /EAP, WPA1/TKIP, LEPS-MAC, LEPS-U
Time Control	time-based activation and deactivation of WLAN networks
Quality of Service	Prioritization according to Wireless Multimedia Extensions (WME, subset of IEEE 802.11e)
Client detection	Rogue WLAN client detection based on probe requests
Space Time Block Coding (STBC)*	Coding method according to IEEE 802.11n. The Space Time Block Coding improves reception by coding the data stream in blocks.
Low Density Parity Check (LDPC)*	Low Density Parity Check (LDPC) is an error correcting method. IEEE 802.11n uses convolution coding (CC) as standard error correcting method, the usage of the more effective Low Density Parity Check (LDPC) is optional.
*) Note	Depends on the access points in operation
Security	
Encryption options	WPA3-Personal, IEEE 802.1X (WPA3-Enterprise, WPA2-Enterprise), IEEE 802.11i (WPA2-Personal), Wi-Fi Certified™ WPA2™, WPA, WEP, IEEE 802.11w (Protected Management Frames), LEPS-MAC (R&S® LANCOM Enhanced Passphrase Security MAC), LEPS-U (R&S® LANCOM Enhanced Passphrase Security User)
Encryption	AES-CCMP AES-GCMP, TKIP, RC4 (only used by WEP)
EAP types (authenticator)	EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, EAP-FAST
RADIUS/EAP-server	User administration MAC-based, rate limiting, passphrases, VLAN user based, authentication of IEEE 802.1X clients via EAP-TLS, EAP-TTLS, EAP-MD5, EAP-GTC, PEAP, MSCHAP, MSCHAPv2, Dynamic Peer Discovery
Others	WLAN protocol filters, IP-redirection of any packet received over the WLAN interface, IEEE 802.1X supplicant, background scanning, client detection ("rogue WLAN client detection"), Wireless Intrusion Detection System (WIDS)
Others	IEEE 802.1X supplicant, background scanning, client detection ("rogue WLAN client detection"), Wireless Intrusion Detection System (WIDS)
R&S® LANCOM Active Radio Control	
Client Management	Steering of WLAN clients to the ideal access point using 802.11k and 802.11v
Band Steering	Steering of 5GHz clients to the corresponding high-performance frequency band
Managed RF Optimization*	Selection of optimal WLAN channels by the administrator

R&S® LANCOM WLC-2000

R&S® LANCOM Active Radio Control	
Adaptive Noise Immunity	Better WLAN throughput due to immunity against interferences
Spectral Scan	Monitoring your WLAN for sources of interference
Adaptive RF Optimization	Dynamic selection of the optimal WLAN channel
Airtime Fairness	Improved utilization of the WLAN bandwidth
*) Note	Depends on the access points in operation. Steering of WLAN clients is not available in US version
WLAN-Controller	
Number of managed devices	Up to 25 R&S® LANCOM Access Points and WLAN routers can be centrally managed by the WLAN controller. Expansion options are available to extend support up to 2000 R&S® LANCOM Access Points and WLAN routers to be managed. Capacities can be expanded even further by clustering multiple controllers
Number of managed SSIDs	Up to 512 SSIDs can be managed by the WLAN controller.
Smart Controller technology	The WLAN controller can switch user data per AP Radio or per SSID in the following ways: – Direct switching to the LAN at the AP (for maximum performance, e.g. for IEEE 802.11n-based access points) – Logical separation of user data into VLANs (e.g. for WLAN guest access accounts) – Central tunneling to the Controller* (layer 3 tunneling between different IP Subnets)
Auto Discovery	R&S® LANCOM access points and WLAN routers automatically discover the WLAN controller by means of DNS name or IP addresses. Even AP's at remote sites or in home offices with no direct access to the Controller can be integrated into the central Controller
Authentication and Authorization	Access Points can be authenticated manually or automatically. Signaling of new access points by LED, e-mail message, SYSLOG and SNMP traps. Manual authentication via LANmonitor or WEBconfig GUI tools. Semi-automatic authentication based on access-point lists in the Controller ('bulk mode'). Fully automatic authentication with default configuration assignment (can be activated/deactivated separately, e.g. during the rollout phase). Authenticated access points can be identified by means of digital certificates; certificate generation by integrated CA (Certificate Authority); certificate distribution by SCEP (Simple Certificate Enrollment Protocol). Access points can be blocked by CRL (Certificate Revocation List).
Management communication protocol	CAPWAP (Control and Provisioning Protocol for Wireless Access Points)
Layer-3 Tunneling	Layer-3 Tunneling in conformity with the CAPWAP standard allows the bridging of WLANs per SSID to a separate IP subnet. Layer-2 packets are encapsulated in Layer-3 tunnels and transported to a R&S® LANCOM WLAN controller. By doing this the access point is independent of the present infrastructure of the network. Possible applications are roaming without changing the IP address and compounding SSIDs without using VLANs
Encryption	DTLS encryption of the control channel between WLAN controller and Access Point (256-bit AES encryption with digital certificates, incl. hardware encryption accelerator; encryption can be disabled for diagnostic purposes).
Firmware deployment	Central Firmware deployment and management of the Access Points. Requires an external web server. Automatic Firmware update on the Access Points is also possible. The Controller checks every day, depending on the defined policy, for the latest Firmware and compares it with the versions in the devices. This can also be activated using Cron jobs. If there is a Firmware mismatch, then the Controller downloads the matching Firmware from the server and updates the corresponding Access Points and Routers.
Script distribution	Enables the complete configuration of non-WLAN specific functions such as Redirects, Protocol Filter, ARF etc. Internal storage of up to three script files (max. 64 kByte) for provisioning access points without a separate HTTP server
RF management and automatic RF optimization	The channel deployment can be static or can be automated. Upon activation of the RF Optimization setting, the Access Points search for an optimal channel in the 2.4 GHz band. The selected channels are sent to the Controller saves these channels on the corresponding Access Points. RF Optimization can also be activated for individual Access Points. Transmit power setting static between 0 to -20 dB. Alarm notification in case of Access Point failure by LED, e-mail, SYSLOG and SNMP traps.
Configuration management	Definition and grouping of all logical and physical WLAN parameters by means of WLAN configuration profiles. Fully automatic or manual profile assignment to WLAN Access Points; automatic transfer and configuration verification (policy enforcement).
Inheritance of configuration profiles	Support of hierarchical WLAN profile groups. New profiles can be easily created by inheriting parameters from existing profiles.
Management operating modes	The AP can be set to 'managed' or 'unmanaged' mode for each radio interface. With R&S® LANCOM WLAN routers, the Controller manages the WLAN part only (split management).

R&S® LANCOM WLC-2000

WLAN-Controller	
Stand alone operation	In 'Managed' mode, an adjustable setting defines the time-span for which the AP continues Stand-alone operation in the event the connection to the Controller fails. After this time-span the AP configuration is deleted and the AP resumes operation only after the connection to the Controller is reestablished. By default this value is set to zero and AP ceases operation as soon as connection to the Controller is lost. Alternatively, a special time setting allows the AP to function in Stand-alone mode indefinitely. In Stand-alone mode only Pre-shared Key SSID's are functional.
VLAN and IP contexts	A fixed VLAN can be set for each SSID. The WLAN controller can independently provide up to 64 separate IP networks, and each of these can be individually mapped to VLANs and, consequently, to SSIDs (Advanced Routing and Forwarding, ARF). The Controller can provide, among others, individual DHCP, DNS, routing, firewall and VPN functions for these networks.
Dynamic VLAN assignment	Dynamic VLAN assignment for target user groups based on MAC addresses, BSSID or SSID by means of external RADIUS server.
RADIUS server	Integrated RADIUS server for MAC address list management. Support for RADSEC (Secure RADIUS) for secure communication with RADIUS servers.
EAP server	Integrated EAP server for authentication of IEEE 802.1X clients via EAP-TLS, EAP-TTLS, EAP-MD5, EAP-GTC, PEAP, MSCHAP or MSCHAPv2
RADIUS/EAP proxy per SSID	Proxy mode for external RADIUS/EAP servers (forwarding and realm handling) per SSID
Redundancy, Controller backup and load balancing	Every managed R&S® LANCOM AP can be assigned to a group of alternative WLAN controllers. A suitable Controller is selected within this group depending on AP load. This ensures that also in backup state the load of larger installations remains equally distributed.
LED control	The LEDs of administrated WLAN devices can be centrally deactivated via the WLAN controller
CA hierarchy	The Certificate Authority (CA) can be structured hierarchically when using multiple WLAN controllers. This allows access points to swap between different WLAN controllers without certificate conflicts. The Certificate Revocation Lists (CRL) can be shared between the different devices
Load balancing	When using multiple WLAN controllers the access points are distributed evenly among the different WLAN controllers to offer the best load balancing. In case one WLAN controller is unavailable the access points are edistributed among the remaining WLAN controllers automatically. Once it is restored they are redistributed again.
Backup	A priority can be set for the WLAN Controller which allows operating in hot standby mode. Access points switch automatically to the WLAN controller with the highest priority
Fast roaming	VoWLAN devices require seamless roaming for ensuring optimal speech quality. The Access Points support PMK caching and Pre-authentication for such demanding applications. WPA2 and WPA2-PSK operate with sub-85 ms roaming times (requirements: adequate signal quality, sufficient RF overlap, clients with a low roaming threshold).
QoS	IEEE 802.11e / WME: Automatic VLAN tagging (IEEE 802.1p) in the Access Points. Mapping to DiffServ attributes in the WLAN controller if this is deployed as a layer-3 router
WLAN visualization	The management tool WLANmonitor acts as a central monitoring program for the WLAN controller and visualizes the performance of all WLAN controllers, Access Points, SSIDs and clients.
WLAN guess access accounts	Static mapping of guest SSIDs in VLANs, access limitations and VLAN routing by means of ARF (Advanced Routing and Forwarding).
Public Spot function	Integrated Public Spot XL-functionality. Easy set-up of guest accounts with just a few mouse clicks using the Voucher-Wizard. The vouchers can be printed over any standard Printer on the network. The Voucher-Wizard can be customized by uploading an individual logo. Function works without external RADIUS and Accounting Servers. Configuration of time and/or traffic budgets as well as when accounting should start. Support of public certificates and certificate chains from trust centers for Public Spots. This allows popular browsers to access trustworthy login pages with secure access (HTTPS) without warnings
WLAN client limiting	To ensure that load is evenly balanced between multiple Access Points, each one can be set with a maximum number of allowable WLAN clients.
Automatic configuration alignment (Config Sync)*	Due to the grouping of several individual devices to one device group (cluster), configuration changes conducted for one device can be automatically synchronized with all cluster devices, without having to manage each device manually (Config Sync).
Management software	LANconfig, LANmonitor, WLANmonitor
*)	Only with WLC Clustering XL Option

R&S® LANCOM WLC-2000

Supported Access Points and WLAN routers	
Indoor	<ul style="list-style-type: none"> ▶ R&S® LANCOM L-151gn Wireless, R&S® LANCOM L-151E Wireless, R&S® LANCOM L-54g Wireless, R&S® LANCOM L-54ag Wireless, R&S® LANCOM L-54 dual Wireless ▶ R&S® LANCOM L-305agn Wireless, R&S® LANCOM L-310agn Wireless, R&S® LANCOM L-315agn dual Wireless ▶ R&S® LANCOM L-320agn Wireless, R&S® LANCOM L-320agn Wireless (white), R&S® LANCOM L-321agn Wireless, R&S® LANCOM L-322agn dual Wireless, R&S® LANCOM L-322E Wireless, R&S® LANCOM L-330agn dual Wireless ▶ R&S® LANCOM L-451agn Wireless, R&S® LANCOM L-452agn dual Wireless, R&S® LANCOM L-460agn dual Wireless ▶ R&S® LANCOM LN-630acn dual Wireless, R&S® LANCOM LN-830acn dual Wireless, R&S® LANCOM LN-830E Wireless, R&S® LANCOM L-822acn dual Wireless, R&S® LANCOM LN-830U, R&S® LANCOM L-1302acn dual Wireless, R&S® LANCOM L-1310acn dual Wireless, R&S® LANCOM LN-860, R&S® LANCOM LN-862 ▶ R&S® LANCOM LN-1700, R&S® LANCOM LN-1702 ▶ R&S® LANCOM LN-1700B, R&S® LANCOM LN-1702B, R&S® LANCOM LN-1700UE ▶ R&S® LANCOM LW-500, R&S® LANCOM LW-600, R&S® LANCOM LW-700 ▶ R&S® LANCOM LX-6200, R&S® LANCOM LX-6200E ▶ R&S® LANCOM LX-6400, R&S® LANCOM LX-6402, R&S® LANCOM LX-6500, R&S® LANCOM LX-6500E ▶ R&S® LANCOM LX-7000 series
Outdoor	<ul style="list-style-type: none"> ▶ R&S® LANCOM OAP-321, R&S® LANCOM OAP-321-3G ▶ R&S® LANCOM OAP-382, R&S® LANCOM OAP-322 ▶ R&S® LANCOM OAP-821, R&S® LANCOM OAP-822, R&S® LANCOM OAP-830 ▶ R&S® LANCOM OAP-1700B, R&S® LANCOM OAP-1702B ▶ R&S® LANCOM OW-602 ▶ R&S® LANCOM OW-702 ▶ R&S® LANCOM OX-6400, R&S® LANCOM OX-6402
Industrial	<ul style="list-style-type: none"> ▶ R&S® LANCOM IAP-321, R&S® LANCOM IAP-321-3G, R&S® LANCOM IAP-322 ▶ R&S® LANCOM IAP-821, R&S® LANCOM IAP-822 ▶ R&S® LANCOM IAP-1781VAW+
UMTS/HSPDA	▶ R&S® LANCOM 1780EW-4G, R&S® LANCOM 1780EW-3G, R&S® LANCOM 1780EW-4G+
WLAN-Router and IADs	<ul style="list-style-type: none"> ▶ R&S® LANCOM 1781VAW, R&S® LANCOM 1781AW, R&S® LANCOM 1781EW(+) ▶ R&S® LANCOM 1783VAW, R&S® LANCOM 883 VoIP ▶ R&S® LANCOM 1793VAW, R&S® LANCOM 1790VAW ▶ R&S® LANCOM 1800VAW, R&S® LANCOM 1800VAW-4G, R&S® LANCOM 1800EFW
Functions in layer-3 routing mode	
Note:	Some of the below functions are only active when the device is operating as a router, firewall or VPN gateway.
Layer 2 features	
VLAN	4.096 IDs based on IEEE 802.1q, dynamic assignment
Quality of Service	WME based on IEEE 802.11e, Wi-Fi Certified™ WMM®
Rate limiting	SSID based, WLAN client based
Multicast	IGMP-Snooping, MLD-Snooping
Protocols	Ethernet over GRE-Tunnel (EoGRE), L2TPv3, ARP-Lookup, LLDP, DHCP option 82, IPv6-Router-Advertisement-Snooping, DHCPv6-Snooping, LDRA (Lightweight DHCPv6 Relay Agent), Spanning Tree, Rapid Spanning Tree, ARP, Proxy ARP, BOOTP, DHCP, LACP
OAM	Ethernet link OAM 802.3ah, IEEE 802.1ag CFM
Layer 3 features	
Firewall	Stateful inspection firewall including packet filtering, extended port forwarding, N:N IP address mapping, packet tagging, support for DNS targets, user-defined rules and notifications

R&S® LANCOM WLC-2000

Layer 3 features	
Quality of Service	Traffic shaping, bandwidth reservation, DiffServ/TOS, packetsize control, layer-2-in-layer-3 tagging, support for 8 QoS queues (6 free configurable)
Security	Intrusion Prevention, IP spoofing, access control lists, Denial of Service protection, detailed settings for handling reassembly, session-recovery, PING, stealth mode and AUTH port, URL blocker, password protection, programmable reset button
PPP authentication mechanisms	PAP, CHAP, MS-CHAP, and MS-CHAPv2
High availability / redundancy	VRRP (Virtual Router Redundancy Protocol)
Router	IPv4-, IPv6-, IPv4/IPv6 dual stack
SD-WAN Application Routing	SD-WAN Application Routing in connection with the R&S®LANCOM Management Cloud
SD-WAN dynamic path selection	SD-WAN dynamic path selection in connection with the R&S®LANCOM Management Cloud
Router virtualization	ARF (Advanced Routing and Forwarding) up to separate processing of 128 contexts
IPv4 services	HTTP and HTTPS server for configuration by web interface, DNS client, DNS server, DNS relay, DNS proxy, dynamic DNS client, DHCP client, DHCP relay and DHCP server including autodetection, NTP client, SNTP server, policy-based routing, Bonjour-Proxy, RADIUS
IPv6 services	HTTP and HTTPS server for configuration by web interface, DHCPv6 client, DHCPv6 server, DHCPv6 relay, DNS client, DNS server, dynamic DNS client, NTP client, SNTP server, Bonjour-Proxy, RADIUS
Dynamic routing protocols	RIPv2, BGPv4, OSPFv2, LISP (Locator/ID Separation Protocol)
IPv4 protocols	DNS, HTTP, HTTPS, ICMP, NTP/SNTP, PPPoE (server), RADIUS, RADSEC (secure RADIUS), RTP, SNMPv1,v2c,v3, TFTP, TACACS+, IGMPv3
IPv6 protocols	NDP, stateless address autoconfiguration (SLAAC), stateful address autoconfiguration (DHCPv6), router advertisements, ICMPv6, DHCPv6, DNS, HTTP, HTTPS, PPPoE, RADIUS, SMTP, NTP, BGP, LISP, Syslog, SNMPv1,v2c,v3, MLDv2, PIM, NPTv6 (NAT66), VRRPv3
Multicast Routing	PIM (Protocol Independent Multicast), IGMP proxy, MLD proxy
WAN operating mode	VDSL, ADSL1, ADSL2 or ADSL2+ additional with external DSL modem at an ETH port
WAN protocols	PPPoE, Multi-PPPoE, ML-PPP, GRE, EoGRE, PPTP (PAC or PNS), L2TPv2 (LAC or LNS), L2TPv3 with Ethernet-Pseudowire, IPoE (using DHCP or no DHCP), RIP-1, RIP-2, VLAN, IPv6 over PPP (IPv6 and IPv4/IPv6 dual stack session), IP(v6)oE (autokonfiguration, DHCPv6 or static)
Tunneling protocols (IPv4/IPv6)	6to4, 6in4, 6rd, Dual Stack Lite, 464XLAT
VPN	
IPSec over HTTPS	Enables IPSec VPN based on TCP (at port 443 like HTTPS) which can go through firewalls in networks where e. g. port 500 for IKE is blocked. Suitable for client-to-site connections and site-to-site connections. IPSec over HTTPS is based on the NCP VPN Path Finder technology
Number of VPN tunnels	Max. number of concurrent active IPSec, PPTP (MPPE) and L2TPv2 tunnels: 5. Unlimited configurable connections.
Hardware accelerator	Integrated hardware accelerator for 3DES/AES encryption and decryption
Realtime clock	Integrated, buffered realtime clock to save the date and time during power failure. Assures timely validation of certificates in any case
Random number generator	Generates real random numbers in hardware, e. g. for improved key generation for certificates immediately after switching-on
1-Click-VPN Site-to-Site	Creation of VPN connections between R&S®LANCOM routers via drag and drop in LANconfig
IKE, IKEv2	IPSec key exchange with Preshared Key or certificate (RSA signature, ECDSA-Signature, digital signature)
Smart Certificate	Convenient generation of digital X.509 certificates via an own certification authority (SCEP-CA) on the webpage or via SCEP.
Certificates	X.509 digital multi-level certificate support, compatible with Microsoft Server / Enterprise Server and OpenSSL. Secure Key Storage protects a private key (PKCS#12) from theft.
Certificate rollout	Automatic creation, rollout and renewal of certificates via SCEP (Simple Certificate Enrollment Protocol) per certificate hierarchy

R&S® LANCOM WLC-2000

VPN	
Certificate revocation lists (CRL)	CRL retrieval via HTTP per certificate hierarchy
OCSP Client	Check X.509 certifications by using OCSP (Online Certificate Status Protocol) in real time as an alternative to CRLs
OCSP Server / Responder	Offers validity information for certificates created with Smart Certificate via OCSP
XAUTH	XAUTH client for registering R&S® LANCOM routers and access points at XAUTH servers incl. IKE-config mode. XAUTH server enables clients to register via XAUTH at R&S® LANCOM routers. Connection of the XAUTH server to RADIUS servers provides the central authentication of VPN-access with user name and password. Authentication of VPN-client access via XAUTH and RADIUS connection additionally by OTP token
Proadaptive VPN	Automated configuration and dynamic creation of all necessary VPN and routing entries based on a default entry for site-to-site connections.
Algorithms	3DES (168 bit), AES-CBC and -GCM (128, 192 or 256 bit), RSA (1024-4096 bit), ECDSA (P-256-, P-384-, P-521-curves) and Chacha20-Poly 1305. OpenSSL implementation with FIPS-140 certified algorithms. MD-5, SHA-1, SHA-256, SHA-384 or SHA-512 hashes
NAT-Traversal	NAT-Traversal (NAT-T) support for VPN over routes without VPN passthrough
MOBIKE	IKEv2 VPN clients can seamlessly switch between different networks (e.g. from WLAN to mobile radio) without having to re-establish the VPN tunnel
Dynamic DNS	Enables the registration of IP addresses with a Dynamic DNS provider in the case that fixed IP addresses are not used for the VPN connection
Specific DNS forwarding	DNS forwarding according to DNS domain, e.g. internal names are translated by proprietary DNS servers in the VPN. External names are translated by Internet DNS servers
Split DNS	Allows the selective forwarding of traffic for IKEv2 depending on the addressed DNS domain.
IPv4 VPN	Connecting private IPv4 networks
IPv4 VPN over IPv6 WAN	Use of IPv4 VPN over IPv6 WAN connections
IPv6 VPN	Connecting private IPv6 networks
IPv6 VPN over IPv4 WAN	Use of IPv6 VPN over IPv4 WAN connections
Radius	RADIUS authorization and accounting, outsourcing of VPN configurations in external RADIUS server in IKEv2, RADIUS CoA (Change of Authorization)
High Scalability VPN (HSVPN)	Transmission of multiple, securely separated networks within a VPN tunnel
Advanced Mesh VPN	On demand dynamic VPN tunnel establishment between branches
Content Filter (optional)	
Demo version	Activate the 30-day trial version after free registration under http://www.lancom-systems.com/routeroptions
URL filter database/rating server*	Worldwide, redundant rating servers from IBM Security Solutions for querying URL classifications. Database with over 100 million entries covering about 10 billion web pages. Web crawlers automatically search and classify web sites to provide nearly 150,000 updates per day: They use text classification by optical character recognition, key word searches, classification by word frequency and combinations, web-site comparison of text, images and page elements, object recognition of special characters, symbols, trademarks and prohibited images, recognition of pornography and nudity by analyzing the concentration of skin tones in images, by structure and link analysis, by malware detection in binary files and installation packages
URL check*	Database based online check of web sites (HTTP/HTTPS). HTTPS websites are checked based on DNS names of HTTPS server certificates or based on "Reverse DNS lookup" of IP addresses.
Categories/category profiles*	Filter rules can be defined in each profile by collecting category profiles from 58 categories, for example to restrict Internet access to business purposes only (limiting private use) or by providing protection from content that is harmful to minors or hazardous content (e.g. malware sites). Clearly structured selection due to the grouping of similar categories. Content for each category can be allowed, blocked, or released by override
Override**	Each category can be given an optional manual override that allows the user to access blocked content on a case-by-case basis. The override operates for a limited time period by allowing the category or domain, or a combination of both. Optional notification of the administrator in case of overrides

R&S® LANCOM WLC-2000

Content Filter (optional)	
Black-/whitelist	Lists that are manually configured to explicitly allow (whitelist) or block (blacklist) web sites for each profile, independent of the rating server. Wildcards can be used when defining groups of pages or for filtering sub pages
Profiles	Timeframes, blacklists, whitelists and categories are collected into profiles that can be activated separately for content-filter actions. A default profile with standard settings blocks racist, pornographic, criminal, and extremist content as well as anonymous proxies, weapons/military, drugs, SPAM and malware
Time frames	Timeframes can be flexibly defined for control over filtering depending on the time of day or weekday, e.g. to relax controls during break times for private surfing
Flexible firewall action	Activation of the content filter by selecting the required firewall profile that contains content-filter actions. Firewall rules enable the flexible use of your own profiles for different clients, networks or connections to certain servers
Individual display pages (for blocked, error, override)	Response pages displayed by the content filter in case of blocked sites, errors or overrides can be custom designed. Variables enable the inclusion of current information such as the category, URL, and rating-server categorization. Response pages can be issued in any language depending on the language set in the user's web browser
Redirection to external pages	As an alternative to displaying the device's own internal response pages to blockings, errors or overrides, you can redirect to external web servers
License management	Automatic notification of license expiry by e-mail, LANmonitor, SYSLOG or SNMP trap. Activation of license renewal at any time before expiry of the current license (the new licensing period starts immediately after expiry of the current license)
Statistics	Display of the number of checked and blocked web pages by category in LANmonitor. Logging of all content-filter events in LANmonitor; log file created daily, weekly or monthly. Hit list of the most frequently called pages and rating results. Analysis of the connection properties; minimum, maximum and average rating-server response time
Notifications	Messaging in case of content-filter events optionally by e-mail, SNMP, SYSLOG or LANmonitor
Wizard for typical configurations	Wizard sets up the content filters for a range of typical scenarios in a few simple steps, including the creation of the necessary firewall rules with the corresponding action
Max. users	Simultaneous checking of HTTP(S) traffic for a maximum of 400 different IP addresses in the LAN
*) Note	Categorization is maintained by IBM. Neither IBM or R&S®LANCOM can guarantee full accuracy of the categorization.
***) Note	The Override function is only available for HTTP websites.
VoIP	
SIP ALG	The SIP ALG (Application Layer Gateway) acts as a proxy for SIP communication. For SIP calls the ALG opens the necessary ports for the corresponding media packets. Automatic address translation (STUN is no longer needed).
Interfaces	
Ethernet ports	6 ETH ports (10/100/1000 Mbps Ethernet), and two SFP+ ports (10 GBit/s); up to 5 ports can be operated as additional WAN ports with load balancing. Ethernet ports can be electrically disabled within LCOS configuration. The R&S®LANCOM GPON-SFP-1 module supports up to 1Gbps when installed in an SFP+ port.
Port configuration	Each Ethernet port can be freely configured (LAN, DMZ, WAN, monitor port, off). Additionally, external DSL modems or termination routers can be operated as a WAN port with load balancing and policy-based routing.
USB 3.0 host port	2x USB 3.0 host port for connecting USB printers (USB print server), serial devices (COM port server), USB data storage (FAT file system); bi-directional data exchange is possible
Serial interface	Serial configuration interface / COM port (RJ-45): 9,600 - 115,000 baud.
Management and monitoring	
Management	LANconfig, WEBconfig, R&S®LANCOM Layer 2 management (emergency management)
Management functions	Alternative boot configuration, voluntary automatic updates for LCMS and LCOS, individual access and function rights up to 16 administrators, RADIUS and RADSEC user management, remote access (WAN or (W)LAN, access rights (read/write) adjustable separately), SSL, SSH, HTTPS, Telnet, TFTP, SNMP, HTTP, access rights via TACACS+, scripting, timed control of all parameters and actions through cron job
FirmSafe	Two stored firmware versions, incl. test mode for firmware updates

R&S® LANCOM WLC-2000

Management and monitoring	
automatic firmware update	configurable automatic checking and installation of firmware updates
Monitoring	R&S® LANCOM Management Cloud, LANmonitor, WLANmonitor
Monitoring functions	Device SYSLOG, SNMPv1,v2c,v3 incl. SNMP-TRAPS, extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, internal logging buffer for firewall events
Monitoring statistics	Extensive Ethernet, IP and DNS statistics; SYSLOG error counter, accounting information exportable via LANmonitor and SYSLOG, Layer 7 Application Detection including application-centric tracking of traffic volume
IPerf	IPerf is a tool for measurements of the bandwidth on IP networks (integrated client and server)
SLA-Monitor (ICMP)	Performance monitoring of connections
Netflow	Export of information about incoming and outgoing IP traffic
Hardware	
Weight	3,5 kg
Power supply	Internal power supply unit (110–230 V, 50-60 Hz)
Environment	Temperature range 0–40° C; humidity 0–85%; non-condensing
Housing	Robust metal housing, 19" 1 HU (440 x 44 x 269,2 mm, W x H x D), with removable mounting brackets, network connectors on the front
Fans	2
Power consumption (max.)	60 watt
Declarations of conformity*	
CE	EN 62368, EN 55022, EN 55024
Scope of delivery	
Cable	IEC power cord (Type F)
Support	
Warranty extension	Free warranty extension up to 3 years (replacement service for defects) Find details here . The service and support conditions valid as of July 1, 2026, available at rs-nc.rohde-schwarz.com/fileadmin/pdf/LCS/ServiceSupportConditions/Rohde-Schwarz-Networks-and-Cybersecurity-GmbH-Service-and-Support-Conditions-20260701.pdf , apply.
Security updates	Up to 2 years after End of Sale of the device (but min. 3 years, see Link), can be extended by purchasing R&S® NC Support products
Software updates	Regular free updates including new features as part of the R&S® NC Lifecycle Management (Link)
Information on the EU Data Act	For details on product data and data on connected services, please refer to: Link
Manufacturer support	Technical manufacturer support as part of a support contract (R&S® NC Community partner, R&S® NC Support Direct, or R&S® NC Support Premium)
R&S® NC Replacement Basic L	Security updates until EOL (min. 5 years) and 5 years replacement service with shipment of the replacement device within 5 days after arrival of the defective device (8/5/5Days), item no. 10722
R&S® NC Replacement Advanced L	Security updates until EOL (min. 5 years) and 5 years NBD advance replacement with delivery of the replacement device within one business day (8/5/NBD), item no. 10732
R&S® NC Support Direct 24/7 L	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10758, 10759 or 10760)
R&S® NC Support Direct Advanced 24/7 L	Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, NBD advance replacement with delivery of the device on the next business day (24/7/NBD), guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10782, 10783 or 10784)


R&S® LANCOM WLC-2000

Support	
R&S®NC Support Direct 10/5 L	Direct, prioritized 10/5 manufacturer support and security updates for the device, guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10746, 10747 or 10748)
R&S®NC Support Direct Advanced 10/5 L	Direct, prioritized 10/5 manufacturer support and security updates for the device, NBD advance replacement with delivery of the device on the next business day (10/5/NBD), guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10770, 10771 or 10772)
Software	
Lifecycle Management	After discontinuation (End of Sale), the device is subject to the R&S®NC Lifecycle Management. Details can be found at: Link
IT Security made in Germany	The development and quality assurance take place in Germany in accordance with high security standards. The „IT Security made in Germany“ quality label of the German IT Security Association attests to the level of security achieved.
Options	
R&S®LANCOM Security Essentials	R&S®LANCOM Security Essentials D Option 1-Year (for R&S®LANCOM SD-WAN central site gateways ISG-5000 and ISG-8000 as well as WLAN controller R&S®LANCOM WLC-2000), item no. 62174
R&S®LANCOM Security Essentials	R&S®LANCOM Security Essentials D Option 3-Years (for R&S®LANCOM SD-WAN central site gateways ISG-5000 and ISG-8000 as well as WLAN controller R&S®LANCOM WLC-2000), item no. 62174
R&S®LANCOM Security Essentials	R&S®LANCOM Security Essentials D Option 5-Years (for R&S®LANCOM SD-WAN central site gateways ISG-5000 and ISG-8000 as well as WLAN controller R&S®LANCOM WLC-2000), item no. 62175
R&S®LANCOM BPjM Filter	R&S®LANCOM BPjM Filter Option, 5 years subscription, item no. 61418
R&S®LANCOM Public Spot PMS Accounting Plus	Extension of the R&S®LANCOM Public Spot (XL) Option for the connection to hotel billing systems with FIAS interface (such as Micros Fidelio) for authentication and billing of guest accesses for 178x/19xx routers, 2100EF, WLCs, and current central-site gateways, item no. 61638
R&S®LANCOM WLC AP Upgrade +10	R&S®LANCOM WLC AP Upgrade +10 Option, enables your WLC to manage 10 Access Points/WLAN router in addition, item no. 61630
R&S®LANCOM WLC AP Upgrade +25	R&S®LANCOM WLC AP Upgrade +25 Option, enables your WLC to manage 25 Access Points/WLAN router in addition, item-no. 61631
R&S®LANCOM WLC AP Upgrade +100	R&S®LANCOM WLC AP Upgrade +100 Option, enables your WLC to manage 100 Access Points/WLAN router in addition, item-no. 61632
R&S®LANCOM WLC AP Upgrade +500	R&S®LANCOM WLC AP Upgrade +500 Option, enables your WLC to manage 500 Access Points/WLAN router in addition, item.-no. 61627
R&S®LANCOM WLC High Availability Clustering XL Option	Comfortable administration of cluster devices like one single device — even at networks across locations, item no. 61636
*) Note	Further details on R&S®LANCOM Service Packs are available at the following Internet address: Link
Accessories	
1000Base-BX20-U SFP module	R&S®LANCOM SFP-AON-1, item no. 60200
10GBASE-BX20-U SFP module	R&S®LANCOM SFP-AON-10, item no. 60211
GPON ONT SFP module	R&S®LANCOM SFP-GPON-1, Compatible for the use on FTTH-lines of Deutsche Telekom, item no. 60199
XGS-PON ONT SFP module	R&S®LANCOM SFP-XGSPON-1, Compatible for the use on FTTH-lines of Deutsche Telekom, item no. 60207
1000Base-BX20 SFP module pair	R&S®LANCOM SFP-BiDi1550-SC1, item no. 60201
1000Base-SX SFP module, 550 m	R&S®LANCOM SFP-SX-LC1, item no. 61556

LCOS 10.94

R&S® LANCOM WLC-2000

Accessories	
1000Base-SX SFP module, 550 m (Bulk 10)	R&S® LANCOM SFP-SX-LC1 (Bulk 10), item no. 60184
1000Base-SX SFP module, 2 km	R&S® LANCOM SFP-SX2-LC1, item no. 60183
1000Base-LX SFP module	R&S® LANCOM SFP-LX-LC1, item no. 61557
1000Base-LX SFP module (Bulk 10)	R&S® LANCOM SFP-LX-LC1 (Bulk 10), item no. 60185
10GBASE-SR/SW SFP module	R&S® LANCOM SFP-SX-LC10, item no. 61485
10GBASE-LR/LW SFP module	R&S® LANCOM SFP-LX-LC10, item no. 61497
10GBASE-ER SFP module	R&S® LANCOM SFP-LR40-LC10, item no. 60182
Direct attach cable	R&S® LANCOM SFP-DAC10-1m, item no. 61495
Direct attach cable	R&S® LANCOM SFP-DAC10-3m, item no. 60175
SFP copper module 1G	R&S® LANCOM SFP-CO1, item no. 61494
SFP copper module 1G (Bulk 10)	R&S® LANCOM SFP-CO1 (Bulk 10), item no. 60186
R&S® LANCOM Power Cord (UK)	IEC power cord, UK plug, item no. 61650
R&S® LANCOM Power Cord (US)	IEC power cord, US plug, item no. 61651
R&S® LANCOM Power Cord (CH)	IEC power cord, CH plug, item no. 61652
R&S® LANCOM Power Cord (AU)	IEC power cord, AU plug, item no. 61653
*) Note	Support for third-party accessories (SFP and DAC) is excluded and cannot be granted
Item number(s)	
R&S® LANCOM WLC-2000	62235



Rohde & Schwarz Networks and Cybersecurity GmbH
 Adenauerstr. 20/B2
 52146 Wuerselen | Germany
info.rs-nc@rohde-schwarz.com | www.rohde-schwarz.com/networks-and-cybersecurity

R&S and Rohde & Schwarz are trademarks of Rohde & Schwarz GmbH & Co. KG, registered or used, among others, in Germany, the EU, the USA, China, and other countries. Other names or designations used may be registered trademarks of different companies or owners. This document contains forward-looking statements regarding products and product features. The publisher reserves the right to change these at any time without stating reasons. No liability is accepted for technical inaccuracies or omissions. 06/2026

ROHDE & SCHWARZ
 Make ideas real

